

Method and arrangement for assessing the quality of skin print images

10/525836

DT01 Rec'd PCT/PTC 25 FEB 2005

The invention relates to a method of assessing the quality of skin print images, and particularly fingerprint images. The invention further relates to an arrangement for carrying out a method of this kind.

When images are made of fingerprints or other skin prints, there may be various factors that have an adverse effect on their quality and, both when a set of reference prints is being assembled and when fingerprints are subsequently checked or identified, these may cause problems that either make any checking or identification impossible or may even lead to erroneous results. Depending on the principle and construction of the sensors used, the quality of the images made may be adversely affected by dirt or moisture, grease on the finger, or a finger that is too dry. Dirt and fouling in or on the sensor itself is another possible cause of images of poor quality of prints from the skin. Added to this, there is also the possibility of incorrect operation by the user himself.

Inferior quality images of skin prints generally result in the images being rejected but, if the worst comes to the worst, they may result in the system being compromised if, due to its poor quality, the skin print is wrongly accepted as correct. It is therefore important to be able to assess the quality of the image that is made of a fingerprint.

It is therefore an object of the present invention to specify a method of determining the quality of images of skin prints, and particularly of fingerprint images. It is also an object of the invention to provide an arrangement for carrying out a method of this kind.

This object is achieved, in accordance with the invention, in that gradients are formed for the individual picture elements (pixels) of the skin print images, in that a mean value is formed from the gradients of the pixels in one region of the image (tile) at a time, and in that similarities in the mean values from tile to tile form a measure of quality.

In calculating gradients, which in the end are to specify the directions of the ridges, also gradients in the opposite direction are calculated, though these too in the end represent an identical direction of the ridges. To eliminate the sign when this is done, provision is made in an advantageous embodiment of the invention for the gradients formed

initially, which have the components $g_{x(alt)}$ and $g_{y(alt)}$, to be squared after the fashion of complex numbers by the formulas $g_x = g_{x(alt)}^2 - g_{y(alt)}^2$ and $g_y = 2g_{x(alt)} * g_{y(alt)}$.

It is assumed for the purposes of the invention that in skin print images the direction of the ridges changes only slightly from one tile to the adjacent one. This
5 presupposes that the complete skin print image is divided into a sufficiently large number of tiles, which is necessary anyway for a later analysis, and in particular for an extraction of the characteristic features. In this way, the size of the tiles may be 10 x 10 pixels, for example.

A particularly advantageous manner of determining whether the mean values change to a greater or lesser degree from tile to tile comprises, in another embodiment,
10 entering the mean values in two directional matrices for x and y, in that scalar products are formed of the directional matrices together with the matrices that are displaced horizontally, vertically and in the directions of both diagonals by one tile, in that each of the products that were obtained in that way by multiplying the matrices are summed over all the tiles, and in that the sums are added together and are divided by the sum of the scalar products of the
15 directional matrices with themselves in order to form the quality measure, said sum of the scalar products of the directional matrices with themselves being summed up over all tiles.

The sensor usually covers a rectangular area, in which case the finger does not rest on the sensor in the edge or corner regions. The areas that are thus not occupied by the finger may in certain cases prove a nuisance when quality is being assessed. This is not so
20 much the case with sensors in which the areas not occupied by the finger, i.e. the areas lying outside what is termed the region of interest (ROI), are homogeneous. However, use is also made of sensors that produce a raster pattern or stripes outside the region of interest. With sensors of this type, it is advisable for the assessment of quality to be confined to the region of interest.

25 To enable the region of interest to be determined for this purpose, provision may be made, in another embodiment, for the lengths of the gradients for which mean values have been formed to be used to determine a region of interest of the skin print that has been scanned.

The arrangement according to the invention is advantageously arranged to
30 have digital signal processing means to perform the method steps according to the invention. Recourse may be had in this case to systems that are known per se for individual steps of the signal processing.

These and other aspects of the invention are apparent from and will be elucidated with reference to the embodiments described hereinafter.

In the drawings:

Fig. 1 is a diagrammatic representation of the gradients determined within
5 a tile.

Fig. 2 shows mean values of the gradients determined over respective tiles, for
the entire image, and

Fig. 3 shows equations for calculating the quality measure.

10

For the sake of clarity, the tile 1 shown in Fig. 1 has only 4 x 4 pixels. Within
the tile there are - once again as a major simplification - parts of two ridges 2, 3 that, for the
purposes of the rules relating to drawings for patents, have been shown as hatched bars. Also,
no allowance has been made in the representation either for the characteristic followed by the
15 gray levels or for any local quantization by the scanning process. For each pixel, there is
calculated by methods that are known per se a gradient 4 that - as described above - does not
depend on the sign of the edges of the ridges 2, 3. Since the ridges do not have a particularly
pronounced curvature at the majority of points in the skin print image, the gradients assume
substantially similar directions.

20

The length of the gradients too is not a faithful representation of reality. It has
merely been indicated that the gradients may be of different lengths. For further processing,
the components in the x and y directions are placed in respective directional matrices.

As an illustration, Fig. 2 shows the entire image of a skin print containing
representative mean values of the gradients calculated for respective ones of the tiles 1.

25

As already mentioned, the region of interest 5 does not cover the whole of the
area scanned by the sensor. If the sensor used is one that, outside the region of interest 5,
produces a homogeneous signal, such as black or white for example, then it is perfectly
possible for the entire area 6 to be covered in the subsequent steps of the method according to
the invention. In the tiles that are situated outside the region of interest, the mean values
30 obtained for the gradients then become zero and hence are no nuisance. The same is true for
tiles of which only part is situated in the region of interest 5.

To form the quality measure, an autocorrelation is performed of the mean
values g. For this purpose, scalar products A_x , A_y , A_{xy} and A_{yx} are formed using the equations

shown in Fig. 3. Also, the value A is derived as a center for the autocorrelation. The quality measure Q is then calculated as $Q = (A_x + A_y + A_{xy} + A_{yx})/4A$.

The summing is performed in each case for the entire area δ , namely from $k=1$ and $l=1$ to their maximum values.

CLAIMS:

1. A method of assessing the quality of skin print images, and particularly fingerprint images, characterized in that gradients are formed for the individual picture elements (pixels) of the skin print images, in that a mean value is formed from the gradients of the pixels in one region of the image (tile) at a time, and in that similarities in the mean values from tile to tile form a measure of quality.
5
2. A method as claimed in claim 1, characterized in that the gradients formed initially, which have the components $g_{x(alt)}$ and $g_{y(alt)}$, are squared after the fashion of a complex number by the formulas $g_x = g_{x(alt)}^2 - g_{y(alt)}^2$ and $g_y = 2g_{x(alt)} * g_{y(alt)}$.
10
3. A method as claimed in either of claims 1 and 2, characterized in that the mean values are entered in two directional matrices for x and y, in that scalar products are formed of the directional matrices together with the matrices that are displaced horizontally, vertically and in the directions of both diagonals by one tile, in that each of the products that were obtained in that way by multiplying the matrices are summed over all the tiles, and in that the sums are added together and are divided by the sum of the scalar products of the directional matrices with themselves in order to form the quality measure, said sum of the scalar products of the directional matrices with themselves being summed up over all tiles.
15
4. A method as claimed in any of claims 1 to 3, characterized in that the lengths of the average gradients are used to determine a region of interest of the skin print that has been scanned.
20
5. An arrangement for assessing the quality of skin print images, and particularly fingerprint images, characterized by a system for forming
25
gradients for the individual picture elements (pixels) of the skin print image,
a mean value from the gradients of the pixels in one region of the image (tile)
at a time, and
a measure of quality from similarities in the mean values from tile to tile.

6. An arrangement as claimed in claim 5, characterized in that the system for forming the gradients for the individual picture elements (pixels) of the skin print image and for forming the mean value from the gradients of the pixels in one region of the image (tile) at a time is arranged to square initially formed gradients, which have the components $g_{x(alt)}$ and $g_{y(alt)}$, after the fashion of a complex number by the formulas $g_x = g_{x(alt)}^2 - g_{y(alt)}^2$ and $g_y = 2g_{x(alt)} * g_{y(alt)}$.

7. An arrangement as claimed in either of claims 5 or 6, characterized in that the system for forming the measure of quality from similarities in the mean values from tile to tile is arranged

to enter the mean values in two directional matrices for x and y,

to form scalar products of the directional matrices having matrices that are displaced horizontally, vertically and in the directions of both diagonals by one tile,

to sum, over all the tiles, each of the products that are obtained by multiplying the matrices, and

to form the quality measure by adding the sums together and dividing the scalar products of the directional matrices, said scalar products having been summed over all the tiles, by themselves.

8. An arrangement as claimed in any of claims 5 to 7, characterized in that the system for forming gradients for the individual picture elements (pixels) of the skin print image and for forming a mean value from the gradients of the pixels in one region of the image (tile) at a time is arranged to determine, from the lengths of the averages gradients, a region of interest of the skin print that has been scanned.

ABSTRACT:

In a method and an arrangement for assessing the quality of skin print images, and particularly fingerprint images, provision is made for gradients to be formed for the individual picture elements (pixels) of the skin print image, for a mean value to be formed from the gradients of the pixels in one region of the image (tile) at a time, and for similarities
5 in the mean values from tile to tile to form a measure of quality.

Fig. 1

1/2




FIG. 1




FIG. 2

2/2

$$\begin{aligned}
 A_x &= \sum_{k,l=1}^{\max-1} \left\langle \begin{pmatrix} (g_x)_{k,l} \\ (g_y)_{k,l} \end{pmatrix}, \begin{pmatrix} (g_x)_{k+1,l} \\ (g_y)_{k+1,l} \end{pmatrix} \right\rangle, & A_y &= \sum_{k,l=1}^{\max-1} \left\langle \begin{pmatrix} (g_x)_{k,l} \\ (g_y)_{k,l} \end{pmatrix}, \begin{pmatrix} (g_x)_{k,l+1} \\ (g_y)_{k,l+1} \end{pmatrix} \right\rangle, \\
 A_{xy} &= \sum_{k,l=1}^{\max-1} \left\langle \begin{pmatrix} (g_x)_{k,l} \\ (g_y)_{k,l} \end{pmatrix}, \begin{pmatrix} (g_x)_{k+1,l+1} \\ (g_y)_{k+1,l+1} \end{pmatrix} \right\rangle, & A_{yx} &= \sum_{k,l=1}^{\max-1} \left\langle \begin{pmatrix} (g_x)_{k+1,l} \\ (g_y)_{k+1,l} \end{pmatrix}, \begin{pmatrix} (g_x)_{k,l+1} \\ (g_y)_{k,l+1} \end{pmatrix} \right\rangle, \\
 A &= \sum_{k,l=1}^{\max} \left\langle \begin{pmatrix} (g_x)_{k,l} \\ (g_y)_{k,l} \end{pmatrix}, \begin{pmatrix} (g_x)_{k,l} \\ (g_y)_{k,l} \end{pmatrix} \right\rangle
 \end{aligned}$$

FIG.3

INTERNATIONAL SEARCH REPORT

International Application No
PCT/IB 03/03694

A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 G06K9/00

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 7 G06K

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, INSPEC

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
P,X	<p>EYUNG LIM ET AL: "Fingerprint quality and validity analysis" PROCEEDINGS 2002 INTERNATIONAL CONFERENCE ON IMAGE PROCESSING. ICIP 2002. ROCHESTER, NY, SEPT. 22 - 25, 2002, INTERNATIONAL CONFERENCE ON IMAGE PROCESSING, NEW YORK, NY: IEEE, US, vol. 2 OF 3, 22 September 2002 (2002-09-22), pages 469-472, XP010607362 ISBN: 0-7803-7622-6 abstract; figures 1,5,6; table 1 page 469, right-hand column, paragraph 3 -page 470, left-hand column, paragraph 4 page 471, left-hand column, paragraph 3 --- -/--</p>	1,4,5,8

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
- *Z* document member of the same patent family

Date of the actual completion of the international search

3 November 2003

Date of mailing of the international search report

18/12/2003

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3018

Authorized officer

Müller, M

INTERNATIONAL SEARCH REPORT

International Application No
PCT/IB 03/03694

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 5 963 656 A (YAO YI-SHENG ET AL) 5 October 1999 (1999-10-05) abstract column 3, line 30 - line 50 column 5, line 35 -column 8, line 65 -----	1,5
A	LINLIN SHEN ET AL: "Quality measures of fingerprint images" AUDIO- AND VIDEO-BASED BIOMETRIC PERSON AUTHENTICATION. THIRD INTERNATIONAL CONFERENCE, AVBPA 2001. PROCEEDINGS (LECTURE NOTES IN COMPUTER SCIENCE VOL.2091), AUDIO- AND VIDEO-BASED BIOMETRIC PERSON AUTHENTICATION. THIRD INTERNATIONAL CONFERENCE, AVBP, pages 266-271, XP002259958 2001, Berlin, Germany, Springer-Verlag, Germany ISBN: 3-540-42216-1 page 266, paragraph 1 -page 267, paragraph 2 page 268, paragraph 4 - paragraph 5 -----	1-8
A	WO 02 35453 A (LEE DEUNGGU ;ALPHA ENGINEERING CO LTD (KR)) 2 May 2002 (2002-05-02) abstract page 4, line 35 -page 5, line 10 -----	1-8
A	RATHA N. K. ET AL.: "Fingerprint Image Quality Estimation" RESEARCH REPORT, IBM T J WATSON RESEARCH CENTER, , December 1999 (1999-12), pages 1-5, XP002259959 Yorktown Heights abstract -----	1-8

INTERNATIONAL SEARCH REPORT

Internati lication No
PCT/IB 03/03694

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 5963656	A	05-10-1999	NONE	
WO 0235453	A	02-05-2002	KR 2001000861 A AU 1104902 A WO 0235453 A1	05-01-2001 06-05-2002 02-05-2002